

Advanced IBM UNIX

Advanced IBM UNIX

Advanced IBM UNIX

AIX Acronym Definition

What does AIX stand for?

The acronym **AIX** stands for **Advanced IBM UNIX** anywhere that links here.

To find other possibilities for the [meaning of AIX](#), look up the [AIX acronym](#) in the [list of acronyms starting with "A"](#).

If you use this [HTML code for acronyms](#) the intended meaning of the acronym will displayed by a pop-up tool-tip whenever anyone positions their mouse over the acronym. It also indicates to text-to-speech (auditory) browsers how to correctly pronounce the acronym.

For verbal rendering, the [pronunciation](#) of the AIX acronym should be:

a i x

This information can be provided to auditory browsers using either an [extended link](#) or [embedded RDF metadata](#).

This is an automatically-generated printer-friendly PDF version of the HTML web page at [Advanced IBM UNIX](#) ← CLICK HERE to get the standard HTML version of this document.

Advanced IBM UNIX Usage

HTML for AIX Acronym

when AIX means Advanced IBM UNIX

New! Now updated with the inheritance rules for the [title attribute](#) in [HTML 5](#)

The easiest way to create HTML code indicating that the acronym **AIX** stands for **Advanced IBM UNIX** is to simply include the acronym in an HTML `<a>` tag and an abbreviation tag (not an [acronym tag](#)):

```
<a href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/" title="Advanced IBM UNIX"
onclick="if (confirm('AIX stands for Advanced IBM UNIX')) return false;"
>
<abbr>AIX</abbr>
</a>
```

This is the recommended code for both HTML 4 browsers and HTML 5 browsers. Some browsers, most notably IE, do not activate help when the title attribute is coded on the `<abbr>` tag, but they do work as expected for titles on the `<a>` tag. The `<abbr>` tag inherits its title attribute from the parent `<a>` tag.

If you are creating HTML code for the definition of **Advanced IBM UNIX**, the meaning of the acronym AIX, then include a [<dfn> definition tag](#) around the [<abbr> abbreviation tag](#) and follow the entire HTML code for the hypertext link with the definition of the term:

```
<p>A <a href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/" title="Advanced IBM UNIX"
onclick="if (confirm('AIX stands for Advanced IBM UNIX')) return false;"
>
<dfn><abbr title="Advanced IBM UNIX">AIX</abbr>
</a> is ...(definition of Advanced IBM UNIX)....</p>
```

The `<dfn>` tag gets the term being defined from the title attribute of the `<abbr>` tag. The result should look like this (hovering your mouse over the AIX acronym shows the expanded meaning of the acronym):

A [AIX](#) is ...(definition of "Advanced IBM UNIX")....

If you are creating HTML code that simply expands the acronym then indicate that it is the AIX acronym which is being defined using an HTML `<dfn>` tag with a title attribute around the `<abbr>` tag and follow the HTML for the hypertext link with the acronym definition:

```
<p>When we use the acronym <a href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/" title="Advanced
IBM UNIX"
onclick="if (confirm('AIX stands for Advanced IBM UNIX')) return false;"
>
<dfn title="AIX"><abbr title="Advanced IBM UNIX">AIX</abbr></dfn>
</a> it is the abbreviation for Advanced IBM UNIX.</p>
```

The result should look like this (hovering your mouse over the AIX acronym shows the definition):

When we use the acronym [AIX](#) it is the abbreviation for Advanced IBM UNIX.

Acronym Vocabulary URI Declaration

Advanced IBM UNIX

For the remaining examples, the Acronym Vocabulary namespace URI needs to be declared for use with element tag names and attribute values. For an HTML web page, the beginning of the file should look like this:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE html [
<!ENTITY at "http://Acronyms.net/terms/">
<!ENTITY av "http://Acronyms.net/vocabulary/">
]>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:av="&av;">
<head>
<style type="text/css">
.hide { display: none }
</style>
```

...
This only needs to be done once per document file.

XLink simple link

First, [declare the vocabulary](#) as shown above. Then, add acronyms as follows:

```
<a href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/" title="Advanced IBM UNIX"
xlink:type="simple"
xlink:href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/"
xlink:arcrole="&av;definedAt"
xlink:role="&av;definition"
xlink:title="Advanced IBM UNIX"
xlink:show="new"
xlink:actuate="onRequest"
>
<abbr
xlink:type="simple"
xlink:href="&at;Advanced-IBM-UNIX"
xlink:arcrole="&av;standsFor"
xlink:role="&av;term"
xlink:title="AIX - Advanced IBM UNIX"
xlink:show="new"
xlink:actuate="onRequest"
>AIX</abbr></dfn>
</a>
```

XLink extended link

First, [declare the vocabulary](#) as shown above. Then, add acronyms as follows:

```
<a xlink:type="extended" href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/" title="Advanced IBM UNIX">
<abbr xlink:type="resource" xlink:label="acronym">AIX</abbr>
<span class="hide" xlink:type="resource" xlink:label="verbal" xlink:title="pronunciation">a i x</span>
<span class="hide" xlink:type="resource" xlink:label="expand" xlink:title="expansion">Advanced IBM UNIX</span>
<span class="hide" xlink:type="locator" xlink:label="term" xlink:role="&av;term" xlink:href="&at;Advanced-IBM-UNIX"
xlink:title="Advanced IBM UNIX"/>
<span class="hide" xlink:type="locator" xlink:label="definition" xlink:role="&av;definition"
xlink:href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/" xlink:title="Advanced IBM UNIX"/>
<span class="hide" xlink:type="locator" xlink:label="finder" xlink:role="&av;reference"
xlink:href="http://www.Acronyms.net/reference/a/AIX#Advanced-IBM-UNIX" xlink:title="AIX - Advanced IBM UNIX"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;pronounceAs" xlink:to="verbal"
xlink:actuate="onLoad"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;expandsTo" xlink:to="expand"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;standsFor" xlink:to="term"/>
<span class="hide" xlink:type="arc" xlink:from="term" xlink:arcrole="&av;definedAt" xlink:to="definition"
xlink:show="new" xlink:actuate="onRequest"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;foundAt" xlink:to="finder"
xlink:show="new" xlink:actuate="onRequest"/>
</a>
```

embedded RDF metadata

First, [declare the vocabulary](#) as shown above. Then, add acronyms as follows:

```
<a href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/" title="Advanced IBM UNIX">
<abbr>AIX</abbr>
</a>
```

Advanced IBM UNIX

URI Reference for Advanced IBM UNIX

URI Reference for Advanced Webmasters

This page is intended for advanced users, such as developers who are creating XML documents or building Semantic Web sites, who want to code their own simple or extended links, or RDF metadata. For all other purposes, the [HTML hypertext links](#), which show the proper usage of URI References, should be used instead.

In RDF or XML documents, refer to the abstract concept of **Advanced IBM UNIX** using this URI reference:

<http://Acronyms.net/terms/a/Advanced-IBM-UNIX>

or, declare the `&at;` entity as shown below and use:

`&at;AdvancedIBMUNIX`

Note that a URI Reference is case-sensitive, and that `www.` is omitted since it is not intended to be a web-accessible resource.

Use the following URL to refer to the web page that defines this term:

<http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX>

Examples

Acronym Vocabulary URI Declaration

The Acronym Vocabulary namespace URI needs to be declared for use with element tag names and attribute values. The beginning of an HTML document should look like this:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE html [
<!ENTITY at "http://Acronyms.net/terms/">
<!ENTITY av "http://Acronyms.net/vocabulary/">
]>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:av="&av;">
<head>
<style type="text/css">
.hide { display: none }
</style>
```

...

This only needs to be done once per document file.

XLink Simple Link

```
<link xlink:href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/" xlink:title="Advanced IBM UNIX"
xlink:type="simple"
xlink:href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/"
xlink:arcrole="&av;definedAt"
xlink:role="&av;definition"
xlink:title="Advanced IBM UNIX"
xlink:show="new"
xlink:actuate="onRequest"
>
<abbr
xlink:type="simple"
xlink:href="&at;Advanced-IBM-UNIX"
xlink:arcrole="&av;standsFor"
xlink:role="&av;term"
xlink:title="AIX - Advanced IBM UNIX"
xlink:show="new"
xlink:actuate="onRequest"
>AIX</abbr>
</link>
```

XLink Extended Link

```
<link xlink:type="extended" xlink:href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/" xlink:title="Advanced
IBM UNIX">
<abbr xlink:type="resource" xlink:label="acronym">AIX</abbr>
<span class="hide" xlink:type="resource" xlink:label="verbal" xlink:title="pronunciation">a i x</span>
<span class="hide" xlink:type="resource" xlink:label="expand" xlink:title="expansion">Advanced IBM UNIX</span>
<span class="hide" xlink:type="locator" xlink:label="term" xlink:role="&av;term" xlink:href="&at;Advanced-IBM-UNIX"
```

Advanced IBM UNIX

```
xlink:title="Advanced IBM UNIX"/>
<span class="hide" xlink:type="locator" xlink:label="definition" xlink:role="&av;definition"
xlink:href="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX/" xlink:title="Advanced IBM UNIX"/>
<span class="hide" xlink:type="locator" xlink:label="finder" xlink:role="&av;reference"
xlink:href="http://www.Acronyms.net/reference/a/AIX#Advanced-IBM-UNIX" xlink:title="AIX - Advanced IBM UNIX"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;pronounceAs" xlink:to="verbal"
xlink:actuate="onLoad"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;expandsTo" xlink:to="expand"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;standsFor" xlink:to="term"/>
<span class="hide" xlink:type="arc" xlink:from="term" xlink:arcrole="&av;definedAt" xlink:to="definition"
xlink:show="new" xlink:actuate="onRequest"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;foundAt" xlink:to="finder"
xlink:show="new" xlink:actuate="onRequest"/>
</link>
```

RDF metadata

```
<rdf:Description rdf:about="...">
<av:standsFor rdf:resource="&at;AdvancedIBMUNIX"/>
</rdf:Description>
<rdf:Description rdf:about="...">
<av:standsFor>
<rdf:Description rdf:about="&at;AdvancedIBMUNIX">
<av:definedBy rdf:resource="http://www.Acronyms.net/terms/a/Advanced-IBM-UNIX"/>
</rdf:Description>
</av:standsFor>
</rdf:Description>
```

This is an automatically-generated printer-friendly PDF version of the HTML web pages at [Advanced IBM UNIX](#) ← CLICK HERE to get the standard HTML version of this document.

