

# Extensible Hypertext Markup Language

## Extensible Hypertext Markup Language

### Extensible Hypertext Markup Language

#### XHTML Acronym Definition

##### What does XHTML stand for?

The acronym **XHTML** stands for **Extensible Hypertext Markup Language** anywhere that links here.

To find other possibilities for the [meaning of XHTML](#), look up the [XHTML acronym](#) in the [list of acronyms starting with "E"](#).

If you use this [HTML code for acronyms](#) the intended meaning of the acronym will displayed by a pop-up tool-tip whenever anyone positions their mouse over the acronym. It also indicates to text-to-speech (auditory) browsers how to correctly pronounce the acronym.

For verbal rendering, the [pronunciation](#) of the XHTML acronym should be:

**x h t m l**

This information can be provided to auditory browsers using either an [extended link](#) or [embedded RDF metadata](#).

This is an automatically-generated printer-friendly PDF version of the HTML web page at [Extensible Hypertext Markup Language](#) ← CLICK HERE to get the standard HTML version of this document.

## Extensible Hypertext Markup Language Usage

#### HTML for XHTML Acronym

##### when XHTML means Extensible Hypertext Markup Language

New! Now updated with the inheritance rules for the [title attribute](#) in [HTML 5](#)

The easiest way to create HTML code indicating that the acronym **XHTML** stands for **Extensible Hypertext Markup Language** is to simply include the acronym in an HTML `<a>` tag and an abbreviation tag (not an [acronym tag](#)):

```
<a href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/" title="Extensible Hypertext Markup Language"
onclick="if (confirm('XHTML stands for Extensible Hypertext Markup Language')) return false;"
>
<abbr>XHTML</abbr>
</a>
```

This is the recommended code for both HTML 4 browsers and HTML 5 browsers. Some browsers, most notably IE, do not activate help when the title attribute is coded on the `<abbr>` tag, but they do work as expected for titles on the `<a>` tag. The `<abbr>` tag inherits its title attribute from the parent `<a>` tag.

If you are creating HTML code for the definition of **Extensible Hypertext Markup Language**, the meaning of the acronym XHTML, then include a [<dfn> definition tag](#) around the [<abbr> abbreviation tag](#) and follow the entire HTML code for the hypertext link with the definition of the term:

```
<p>A <a href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/" title="Extensible Hypertext Markup Language"
onclick="if (confirm('XHTML stands for Extensible Hypertext Markup Language')) return false;"
>
<dfn><abbr title="Extensible Hypertext Markup Language">XHTML</abbr>
</a> is ...(definition of Extensible Hypertext Markup Language)...</p>
```

The `<dfn>` tag gets the term being defined from the title attribute of the `<abbr>` tag. The result should look like this (hovering your mouse over the XHTML acronym shows the expanded meaning of the acronym):

A [XHTML](#) is ...(definition of "Extensible Hypertext Markup Language")....

If you are creating HTML code that simply expands the acronym then indicate that it is the XHTML acronym which is being defined using an HTML `<dfn>` tag with a title attribute around the `<abbr>` tag and follow the HTML for the hypertext link with the acronym definition:

```
<p>When we use the acronym <a href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/"
title="Extensible Hypertext Markup Language"
onclick="if (confirm('XHTML stands for Extensible Hypertext Markup Language')) return false;"
>
<dfn title="XHTML"><abbr title="Extensible Hypertext Markup Language">XHTML</abbr></dfn>
</a> it is the abbreviation for Extensible Hypertext Markup Language.</p>
```

# Extensible Hypertext Markup Language

The result should look like this (hovering your mouse over the XHTML acronym shows the definition):

When we use the acronym [XHTML](#) it is the abbreviation for Extensible Hypertext Markup Language.

## Acronym Vocabulary URI Declaration

For the remaining examples, the Acronym Vocabulary namespace URI needs to be declared for use with element tag names and attribute values. For an HTML web page, the beginning of the file should look like this:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE html [
<!ENTITY at "http://Acronyms.net/terms/">
<!ENTITY av "http://Acronyms.net/vocabulary/">
]>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:av="&av;">
<head>
<style type="text/css">
.hide { display: none }
</style>
```

...

This only needs to be done once per document file.

## XLink simple link

First, [declare the vocabulary](#) as shown above. Then, add acronyms as follows:

```
<a href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/" title="Extensible Hypertext
Markup Language"
xlink:type="simple"
xlink:href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/"
xlink:arcrole="&av;definedAt"
xlink:role="&av;definition"
xlink:title="Extensible Hypertext Markup Language"
xlink:show="new"
xlink:actuate="onRequest"
>
<abbr
xlink:type="simple"
xlink:href="&at;Extensible-Hypertext-Markup-Language"
xlink:arcrole="&av;standsFor"
xlink:role="&av;term"
xlink:title="XHTML - Extensible Hypertext Markup Language"
xlink:show="new"
xlink:actuate="onRequest"
>XHTML</abbr></dfn>
</a>
```

## XLink extended link

First, [declare the vocabulary](#) as shown above. Then, add acronyms as follows:

```
<a xlink:type="extended" href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/"
title="Extensible Hypertext Markup Language">
<abbr xlink:type="resource" xlink:label="acronym">XHTML</abbr>
<span class="hide" xlink:type="resource" xlink:label="verbal" xlink:title="pronunciation">x h t m l</span>
<span class="hide" xlink:type="resource" xlink:label="expand" xlink:title="expansion">Extensible Hypertext Markup
Language</span>
<span class="hide" xlink:type="locator" xlink:label="term" xlink:role="&av;term"
xlink:href="&at;Extensible-Hypertext-Markup-Language" xlink:title="Extensible Hypertext Markup Language"/>
<span class="hide" xlink:type="locator" xlink:label="definition" xlink:role="&av;definition"
xlink:href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/" xlink:title="Extensible
Hypertext Markup Language"/>
<span class="hide" xlink:type="locator" xlink:label="finder" xlink:role="&av;reference"
xlink:href="http://www.Acronyms.net/reference/e/XHTML#Extensible-Hypertext-Markup-Language"
xlink:title="XHTML - Extensible Hypertext Markup Language"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;pronounceAs" xlink:to="verbal"
xlink:actuate="onLoad"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;expandsTo" xlink:to="expand"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;standsFor" xlink:to="term"/>
<span class="hide" xlink:type="arc" xlink:from="term" xlink:arcrole="&av;definedAt" xlink:to="definition"
```

# Extensible Hypertext Markup Language

```
xlink:show="new" xlink:actuate="onRequest"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;foundAt" xlink:to="finder"
xlink:show="new" xlink:actuate="onRequest"/>
</a>
```

## embedded RDF metadata

First, [declare the vocabulary](#) as shown above. Then, add acronyms as follows:

```
<a href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/" title="Extensible Hypertext
Markup Language">
<abbr>XHTML</abbr>
</a>
```

## URI Reference for Extensible Hypertext Markup Language

### URI Reference for Advanced Webmasters

This page is intended for advanced users, such as developers who are creating XML documents or building Semantic Web sites, who want to code their own simple or extended links, or RDF metadata. For all other purposes, the [HTML hypertext links](#), which show the proper usage of URI References, should be used instead.

In RDF or XML documents, refer to the abstract concept of **Extensible Hypertext Markup Language** using this URI reference:

**<http://Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language>**

or, declare the &at; entity as shown below and use:

**&at;ExtensibleHypertextMarkupLanguage**

Note that a URI Reference is case-sensitive, and that www. is omitted since it is not intended to be a web-accessible resource.

Use the following URL to refer to the web page that defines this term:

**<http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language>**

## Examples

### Acronym Vocabulary URI Declaration

The Acronym Vocabulary namespace URI needs to be declared for use with element tag names and attribute values. The beginning of an HTML document should look like this:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE html [
<!ENTITY at "http://Acronyms.net/terms/">
<!ENTITY av "http://Acronyms.net/vocabulary/">
]>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:av="&av;">
<head>
<style type="text/css">
.hide { display: none }
</style>
```

...

This only needs to be done once per document file.

### XLink Simple Link

```
<link xlink:href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/" xlink:title="Extensible
Hypertext Markup Language"
xlink:type="simple"
xlink:href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/"
xlink:arcrole="&av;definedAt"
xlink:role="&av;definition"
xlink:title="Extensible Hypertext Markup Language"
xlink:show="new"
xlink:actuate="onRequest"
>
<abbr
xlink:type="simple"
xlink:href="&at;Extensible-Hypertext-Markup-Language"
xlink:arcrole="&av;standsFor"
xlink:role="&av;term"
```

# Extensible Hypertext Markup Language

```
xlink:title="XHTML - Extensible Hypertext Markup Language"
xlink:show="new"
xlink:actuate="onRequest"
>XHTML</abbr>
</link>
XLink Extended Link
```

```
<link xlink:type="extended" xlink:href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/"
xlink:title="Extensible Hypertext Markup Language">
<abbr xlink:type="resource" xlink:label="acronym">XHTML</abbr>
<span class="hide" xlink:type="resource" xlink:label="verbal" xlink:title="pronunciation">x h t m l</span>
<span class="hide" xlink:type="resource" xlink:label="expand" xlink:title="expansion">Extensible Hypertext Markup
Language</span>
<span class="hide" xlink:type="locator" xlink:label="term" xlink:role="&av;term"
xlink:href="&at;Extensible-Hypertext-Markup-Language" xlink:title="Extensible Hypertext Markup Language"/>
<span class="hide" xlink:type="locator" xlink:label="definition" xlink:role="&av;definition"
xlink:href="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language/" xlink:title="Extensible
Hypertext Markup Language"/>
<span class="hide" xlink:type="locator" xlink:label="finder" xlink:role="&av;reference"
xlink:href="http://www.Acronyms.net/reference/e/XHTML#Extensible-Hypertext-Markup-Language"
xlink:title="XHTML - Extensible Hypertext Markup Language"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;pronounceAs" xlink:to="verbal"
xlink:actuate="onLoad"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;expandsTo" xlink:to="expand"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;standsFor" xlink:to="term"/>
<span class="hide" xlink:type="arc" xlink:from="term" xlink:arcrole="&av;definedAt" xlink:to="definition"
xlink:show="new" xlink:actuate="onRequest"/>
<span class="hide" xlink:type="arc" xlink:from="acronym" xlink:arcrole="&av;foundAt" xlink:to="finder"
xlink:show="new" xlink:actuate="onRequest"/>
</link>
```

RDF metadata

```
<rdf:Description rdf:about="...">
<av:standsFor rdf:resource="&at;ExtensibleHypertextMarkupLanguage"/>
</rdf:Description>
<rdf:Description rdf:about="...">
<av:standsFor>
<rdf:Description rdf:about="&at;ExtensibleHypertextMarkupLanguage">
<av:definedBy rdf:resource="http://www.Acronyms.net/terms/e/Extensible-Hypertext-Markup-Language"/>
</rdf:Description>
</av:standsFor>
</rdf:Description>
```

This is an automatically-generated printer-friendly PDF version of the HTML web pages at [Extensible Hypertext Markup Language](#) ← CLICK HERE to get the standard HTML version of this document.

